

9300P PoE Remote Airborne Particle Counter

1.2 LPM




The 9300P PoE particle counters provide a range of particle size measurement from 0.3 to 25.0 μm at a flow rate of 1.2 LPM. These sensors allow for efficient particle counting with specifications that exceed the ISO 21501-4 and JIS B9921 calibration standards.

These sensors have 30 user-selectable particle size channels (up to 30 channels optional). Integration into a building automation or facility monitoring system is easy via MODBUS™ TCP/IP over Ethernet or WiFi (802.11 b/g).

9300P: Features and Benefits

- Measures 0.3 μm to 25 μm
- 1.2 LPM flow rate
- Long life laser diode technology
- Measures up to 30 channels of simultaneous data
- Accurate in high particle concentration environments
- Internal vacuum pump
- Internal HEPA filter
- User-selectable channel sizes
- Stores up to 65,000 sample records for on-board data redundancy
- (Optional) temperature and relative humidity probe available
- Connect over MODBUS™ TCP/IP over Ethernet or WiFi (802.11 b/g)
- Complies with ISO 21501-4 and JIS B9921 standards
- Easy to clean and wipe down with minimal particle traps
- Alarm light
- LED Indicators
- Seamless integration into a facility monitoring system
- Lightweight stainless steel enclosure
- 5 year warranty



Specifications

Model	9300P PoE
Size Range	0.3 µm to 25 µm
Size Channels	Factory calibrated at 0.3, 0.5, 1.0, 2.5, 5.0, 10.0 µm
Number of Channels	up to 30 Channels
Counting Efficiency	50% @ 0.3µm; 100% for particles > 0.45 µm per JIS
Flow Rate	1.2 LPM
Concentration Limits	27,000,000 particles/ft³ @ 10% coincidence (per ISO 21501-4), 50,000,000 particles/ft³ @ 10% coincidence (as tested and validated)
Light Source	Long life laser diode
Zero Count	< 1 count / 60 minutes (< 1 particles / 6ft³). No fault count subtraction.
Alarms	Channel alarms on Raw counts, concentrations or mass (alarms on environmental sensors optional)
Calibration	NIST traceable
Vacuum Source	Internal vacuum pump with HEPA filter
Filtered Exhaust	Internal HEPA filter
Airflow	Internally monitored
Configuration/Download	USB mini-B
Alarm	Alarm LED ring
Communication Modes	MODBUS™ TCP/IP over Ethernet or WiFi (802.11 b/g)
Environmental Sensor Standards	(Optional) Temp and RH probe 32° to 122°F (0° to 50°C) ±1°F (0.5°C), 15-90% ±2% relative humidity ISO 21501-4 and JIS B9921
Instrument Calibration	Recommended minimum once per year
External Surface	Stainless steel
Dimensions (L x W x H)	3.59" x 1.80" x 4.86" (9.1 cm x 4.5 cm x 12.3 cm)
Weight	1.71 lb. (780 grams)
Accessories	Operating manual and Instrument Management Software (IMS) on USB flash drive.
Optional Accessories	Printed manual barb fittings, mounting bracket and sample tubing, isokinetic probe, power supply
Buffer Memory	65,000 sample records (rotating buffer) including particle count data and environmental data
Sample Time	1 second to 99 hours
Power	7 - 15 VDC (30 watts) or POE (compliant with IEEE 802.3af)
Operating Conditions	41° to 104°F (5° to 40°C) / 20% to 95% non-condensing
Storage Conditions	32° to 122°F (0° to 50°C) / Up to 98% non-condensing
Warranty	5 year warranty Blower warranty : 1 year

